


















YORK® Mini-Split Product Line


Mini-Split Single-Zone System Selection

Space-saving, energy-saving YORK Mini-Split single-zone air conditioners and heat pumps are the perfect comfort solution for room additions, remodels, and other spaces. Indoor Units are ordered to match the capacity of the Outdoor Units.

Efficiency Rating	Series	Indoor Unit(s)	Rated Capacity (BTU/h) for Outdoor/Indoor Unit Combination							
			9k	12k	18k	24k	30k	36k	42k	48k
Up to 18 SEER	 P Series	 Wall-Mount Unit	208/230V Heat Pump							
Up to 20 SEER2	 P Series New Generation	 Wall-Mount Unit	208/230V Heat Pump							
Up to 20 SEER	 R Series	 4-Way Ceiling Cassette	208/230V Heat Pump							
		 Floor / Ceiling Unit								
		 Ducted Unit								
Up to 23 SEER2	 X Series	 Wall-Mount Unit	208/230V Heat Pump							

CONTROLLER TYPE	Wired Zone Controllers					H-Link Gateway	Wired BACnet Gateway
Indoor Series	Indoor Units for Multi-Zones	P & X	P, P New Generation, X, Indoor Units for Multi-Zones	R	R	P, P New Generation, R, X, Indoor Units for Multi-Zones*	P, P New Generation, R, X, Indoor Units for Multi-Zones*
MODEL	DWCMW	DWCPX2	DWUNI	DWCR	DWCR2	DCAHLA	DCABAS
							

CONTROLLER TYPE	Central Controllers			Remote Controllers <i>standard with unit</i>	
Indoor Series	R, Indoor Units for Multi-Zone	P, P New Generation, R, X, Indoor Units for Multi-Zone	Indoor Units for Multi-Zone	R	P, P New Generation, X
MODEL	DCCRMW	DCCUNI	DRCMW	DRCR	DRCPX
					



EWPE Smart App
See Side 2 for more details.

* When connected to a BACnet building automation system (BAS), all controllers' functions display through the BACnet BAS interface.

YORK® Mini-Split Product Line

Mini-Split Multi-Zone System Selection

Multi-zone systems are designed to provide comfort, uncompromising personal style, and quiet operation to multiple spaces. Choose the style and size from the wide selection of indoor and outdoor units to meet your requirements for layout and design.

Efficiency Rating	Series	Indoor Unit(s)	Rated Capacity (BTU/h) for Indoor Units						
			9k	12k	18k	21k	24k	30k	36k
Up to 16 SEER For 2-5 Zone Heat Pump Systems 18k – 2 zones 24k – 2-3 zones 30k – 2-4 zones 36k – 2-4 zones 42k – 2-5 zones	 M Series 208/230V Heat Pump Rated Capacity 18k - 42k	 Wall-Mount Units	Wall-Mount Units						
			Ducted Units						
Up to 22 SEER For 2-5 Zone Heat Pump Systems 18k – 2 zones 24k – 2-3 zones 30k – 2-4 zones 36k – 2-5 zones 42k – 2-5 zones	 W Series 208/230V Heat Pump Rated Capacity 18k - 42k	 Ducted Units  4-Way Ceiling Cassettes	Ducted Units						
			4-Way Ceiling Cassettes						
Up to 20 SEER2 - Ambient operation down to -31°F For 2-5 Zone Heat Pump Systems 18k – 2 zones 24k – 2-3 zones 36k – 2-4 zones 42k – 2-5 zones	 S Series 208/230V Heat Pump Rated Capacity 18k - 42k	 Floor / Ceiling Units	Floor / Ceiling Units						
			Floor / Ceiling Units						

YORK Mini-Split Multi-Zone Systems can be ordered in a wide range of configurations. For more details, please see the YORK Mini-Split Catalog.



EWPE Smart App

Easily control settings from your smartphone or tablet with the EWPE Smart App available on Google Play or in the App Store. Available for P, P New Generation, and X series. Adapter CS532AH required for P and X.